

DUAL DROP-IN ISOLATOR

FREQUENCY GHz	ISOLATION dB, MIN	INSERTION LOSS dB, MAX	VSWR MAX	POWER, WATTS		MODEL#	DIMENSIONS IN INCHES
				FWD	REV		
0.850 - 0.870	40	0.600	1.250:1	120	100	2E2NU	2.170 X 1.250 X 0.250
0.871 - 0.960	40	0.600	1.250:1	60	60	2E2NV	2.170 X 1.250 X 0.250
0.800 - 1.000	40	0.600	1.250:1	5	5	2E2NW	2.170 X 1.250 X 0.250
0.925 - 0.960	40	0.600	1.250:1	65	30	2E2NX	2.170 X 1.250 X 0.250
1.805 - 1.880	40	0.600	1.250:1	40	40	2E4NS	1.750 X 0.880 X 0.250
1.930 - 1.990	40	0.600	1.250:1	80	80	2E4NT	1.750 X 0.880 X 0.250
2.100 - 2.200	40	0.600	1.250:1	60	20	2E4NU-1	1.750 X 0.880 X 0.250
2.200 - 2.300	40	0.600	1.250:1	60	20	2E4NU-2	1.750 X 0.880 X 0.250
2.300 - 2.400	40	0.600	1.250:1	60	20	2E4NU-3	1.750 X 0.880 X 0.250
2.400 - 2.500	40	0.600	1.250:1	60	20	2E4NU-4	1.750 X 0.880 X 0.250
2.500 - 2.600	40	0.600	1.250:1	60	20	2E4NU-5	1.750 X 0.880 X 0.250
2.600 - 2.700	40	0.600	1.250:1	60	20	2E4NU-6	1.750 X 0.880 X 0.250



TYPICAL PACKAGE DIMENSIONS

